



model  
**DN**

Sliding shower enclosure, or shower trays in recess. Innovative and original sliding system: the movement is guaranteed by sliders that can be settled for a perfect calibration of the door.

**Sliding door**  
**Niche**

collection  
**Gliss**

All the Gliss series shower enclosures have a sliding opening. Ideal solution to optimize space; It is also excellent for preventing drops from falling on the floor when leaving the shower.

The sliding is ensured by special floating pads, adjustable for perfect door calibration. The innovative material guarantees an always perfect movement, thanks to its self-lubricating and self-cleaning properties, tested through years of experience in aggressive working environments.

Discover where to buy this shower enclosure designed by Vismaravetro > [Store locator](#)

## FINISHES

### Glass pane

- 03 - Clear bronze
- 04 - Clear glass
- 06 - Reflecting glass
- 07 - Clear grey
- 08 - Satin glass
- 10 - Crystal Extra-reflex
- 12 - Cristallo extrachiaro
- 14 - Crystal Extra-light satin
- 19 - Cristallo madras
- 29 - Crystal Madras Nuvola



### Decorations

- D50 - D50
- D51 - D51
- D52 - D52
- D54 - D54
- D55 - D55
- D60 - D60
- D61 - D61
- P56 - P56



### Knobs and handles

M10G



### Anodised profiles

- 21 - Bright silver
- 31 - Satin silver



### Varnished profiles

14 - White



## OPTIONAL

- Amico
- Basket
- Alias
- Personal Glass
- Treatment preventing limescale (TPA)
- Virgola
- Screen printed stripe
- Vi.p
- Screen

## PLUS

- Custom Made (cm by cm)
- Magnetic strips
- Sliding system by special floating sliders
- Door with releasable system
- S.M.F. (easily mounting system)
- Certified product CE
- Smart compensation without U profile
- Bonded aluminum supports

# ELEMENTS

that compose  
the model DN



## DN

Sliding shower enclosure, for  
shower trays in recess.

### FEATURES

- Magnetic strips
- Horizontal and vertical adjustment
- Sliding system by special floating sliders
- Door with releasable system
- Product conforming to EN14428:2015 with CE marking
- Possibility to use standard compensating profile AS10
- Extension of 30 mm without wall profile
- S.M.F. (easily mounting system)
- Custom Made (cm by cm)

### DIMENSIONS

- Min 97 - Max 180 cm
- Height 200 cm

### MATERIALS

- Anodised or enamelled aluminium profile.
- Tempered safety glass 8 mm.