



model

GLG+GLM+GLG

Traditional style shower enclosure for 3-sided shower made by an opening element GLM (one 180° pivot door and 2 fixed elements aligned) and two side elements GLG. The top arched profile, the elegant finishes of profiles and glasses, the choice among several refined accessories highlight the decorative attitude of this shower enclosure.

**Pivot door
Wall**

collection
Gold

All the shower enclosures of the Gold series have a hinged door. All models open outwards, some even inwards.

Discover where to buy this shower enclosure designed by Vismaravetro > [Store locator](#)

FINISHES

OPTIONAL

- Screen
- Decorative elements Gold TDG

PLUS

- Luxurious accessories
- Magnetic strips
- Certified product CE
- Profilo di irrigidimento ad arco
- S.M.F. (easily mounting system)
- Custom Made (cm by cm)

ELEMENTS

that compose
the model GLG+GLM+GLG



FEATURES

- Extensible 20 mm
- Horizontal and vertical adjustment
- S.M.F. (easily mounting system)
- Certified product CE
- Custom Made (cm by cm)
- NOTE: Please, always advise the exact dimensions of the installed shower tray and specify if left SX or right DX.

GLG

Fixed panel that can be combined with a door element to obtain a corner or a 3-sided shower enclosure.

DIMENSIONS

- Min 68 - Max 90 cm
- Height 195 cm

MATERIALS

- Anodised aluminium profiles
- Tempered safety glass 8 mm.



FEATURES

- Extensible 40 mm
- Magnetic strips
- Inward and outward opening
- It can be assembled with a fix element GLG to obtain a corner or 3-sided shower enclosure
- S.M.F. (easily mounting system)
- Certified product CE
- Profilo di irrigidimento ad arco
- NOTE: Please, always advise the exact dimensions of the recess X. Please always specify if left SX or right DX opening. For this model GLM, unless specific requests, the dimension of the door is approximately 1/2 of the recess. (max cm. 80).

GLM

Shower enclosure for recessed shower tray. One pivot door 180° and two in line fixed elements.

DIMENSIONS

- Min 120 - Max 179 cm
- Height 195 cm

MATERIALS

- Anodised aluminium profiles
- Tempered safety glass 6 mm for the door
- Tempered safety glass 8 mm for the fix elements